

# **SURE-LITES ALL-PRO | ATLITE**

**EXIT & EMERGENCY** 

Sure-Lites, All-Pro and AtLite offer reliable and code compliant solutions for all your exit and emergency needs.

SURE-LITES EMERGENCY LIGHTING

# Innovative Design. Dependable.



Sure-Lites offers emergency lighting fixtures, exit signs and battery packs, including Chicago and New York code compliant solutions ideal for commercial and industrial applications.

### **SELHP**

### **EMERGENCY LIGHTING**

- · Provides emergency lighting for a minimum of 90 minutes
- · Up to 100 feet of emergency egress coverage
- · Long life LED's with LiFePO4 battery, 3 watts remote capacity
- · Labor savings self-diagnostics option
- · Wall and ceiling mount







### **SEL Series**

### **EMERGENCY LIGHTING**

- Designed to reduce egress system cost and maintenance and improve reliability
- Proprietary adjustable AccuLED Optics™ and injection-molded, high-impact thermoplastic housing
- · Long life LED's, no maintenance nickel cadmium battery
- · EZ hang feature reduces installation time and cost
- · Labor savings self-diagnostics available in SD models









Catalog Number	Description	Finish	Replaces	Fixture Spacing Voltage		Watts	UPC
SEL17	2 Head, NiCad	White	2-5.4W INC. Heads	17 ft.	120-277V	0.78W	080083722143
SEL25	2 Head, NiCad	White	2-9W INC. Heads	35 ft.	120-277V	0.6W/0.64W	080083736669
SEL25SD	2 Head, NiCad, Self-Diagnostics	White	2-9W INC. Heads	25 ft.	120-277V	0.67	080083723027
SEL50	2 Head, NiCad	White	2-12W INC. Heads	59 ft.	120-277V	1W/1.02W	080083733347
SEL50SD	2 Head, NiCad, Self-Diagnostics	White	2-12W INC. Heads	50 ft.	120-277V	1.19	080083733361

coverage.

### **SELW Outdoor Series**

### **EMERGENCY LIGHTING**

- · Code compliant, wet location for outdoor use; Standard 0°C to 40°C temperature rating
- · Designed to reduce egress system cost and maintenance and improve reliability
- Proprietary adjustable AccuLED Optics™; 25 feet of emergency egress coverage
- · Injection-molded, high-impact thermoplastic
- · Long life LED's; No maintenance nickel cadmium battery









	3		
ge	Voltage	Watts	UPC
	400.0771/		T001 3 T000000



# **SURE-LITES** EMERGENCY LIGHTING

# **LPX Series**

### **EXIT SIGNAGE**

- · Injection-molded polycarbonate housing
- · Field-Selectable for single or double face; red or green illumination
- · Snap-out or snap-in chevron directional indicators
- · EZ key external battery disconnect











Catalog Number	Description	Finish	Voltage	Watts	UPC
LPX7	Self Powered, Univ. Red and Green	White	120/277V	0.98W/1.03W	080083532773

### **LPXC SERIES**

### **EMERGENCY LIGHTING**

- · Injection-molded polycarbonate housing
- · Field-Selectable for single or double face; red or green illumination
- · Snap-out or snap-in chevron directional indicators
- · EZ key external battery disconnect









Replaces	Coverage	Voltage	Watts	UPC
2-9W INC Heads	25 ft.	120/277V	3.2 W at 277 V	080083770922

### **CHX Series**

### **EXIT SIGNAGE**

· Chicago code compliant exits are ideal for general purpose applications


2 Heads, Unv. Red and Green, Remote Cap. White

- · Extensive range of field-installed accessories and choice of faces
- · Lens installs from side of fixture for convenient maintenance
- · Steel canopy allows ceiling or end mounting
- · Rear universal pattern knockouts for direct mounting to jbox









# SURE-LITES EMERGENCY LIGHTING

# **SCX Complete Edge Lit Exit**

### **EXIT SIGNAGE**

- · Universal mount: surface ceiling, wall, end mount, recessed ceiling and wall mount
- · Pivot housing for sloped ceiling or back wall mount
- · Single-sided clear and double-sided mirror lens panels included
- · Bright red or green LED sources
- · Battery backup models provide 90 minutes of emergency run time







Catalog Number	Description	Finish	Replaces	Coverage	Voltage	Watts	UPC
SCX70R	Self Powered, Red Aluminum	Satin Aluminum	N/A	N/A	120/277V	3.14	080083277704
SCX70G	Self Powered, Green Aluminum	Satin Aluminum	N/A	N/A	120/277V	2.94	080083277728

### **XR Series**

### **EMERGENCY LIGHTING**

- Emergency light with minimum of 90 minutes runtime; Chicago and New York City compliant
- · 20-gauge sheet metal housing; heads are fully adjustable and 300 lumens each
- · Designed to reduce egress system cost and maintenance and improve reliability
- Proprietary adjustable AccuLED Optics™; No maintenance nickel cadmium battery
- · External battery disconnect and EZ Hang feature reduces installation time and cost









### **EBP Series**

### **EMERGENCY BATTERY PACKS**

- · LED Battery Pack automatically switches to emergency mode when AC power fails
- · Maintains illumination of a fixture for a minimum of 90 minutes
- · UL 924 classified for field retrofit installation
- · Labor savings self-diagnostics available in SD models







LED Emergency Battery Pack


### MarketPro Essentials

Catalog Number	Description	Voltage	Watts	UPC
ES EBPLED7W	LED Emergency Battery Pack	120/277V	7	080083289844
ES EBPLED14W	LED Emergency Battery Pack	120/277V	14	080083289868

52 Cooper Lighting Solutions MarketPro Stock Product Guide

# ALL-PRO EMERGENCY LIGHTING

# Compact Design. Value Focused.



### **APEL Series**

### **EMERGENCY LIGHTING**

- · Emergency light with a minimum of 90 minutes of run time
- · No maintenance nickel cadmium battery
- · Fully adjustable LED heads maximizes design flexibility
- · Components are injection-molded, high impact thermoplastic
- · Universal jbox mounting pattern and snap-fit housing









<sup>\*</sup>Egress coverage with APELH2 + remote head units

### **AP2SQLED30 Series**

#### **EMERGENCY LIGHTING**

- · Next generation square head emergency light
- Provides up to 30 feet of egress coverage for 90 minutes
- · Each adjustable square head outputs 80 lumens
- · No maintenance nickel cadmium battery
- · Universal jbox mounting pattern and snap-fit polycarbonate housing







AP2SQLED30 2 Head, NiCad 30' Egress White 2-9W INC Heads 30 ft. 120/277V 2 at 277V 080083264285	Catalog Number	Description	Finish	Replaces	Coverage	Voltage	Watts	UPC
	AP2SQLED30	2 Head, NiCad 30' Egress	White	2-9W INC Heads	30 ft.	120/277V	2 at 277V	080083264285

# **APWR Series**

### **EMERGENCY LIGHTING**

- · Emergency lighting remote heads unit; Allows for 17 feet of emergency egress coverage
- · Adjustable heads adjust 80° from vertical with 358° rotation
- · Wet location listed and can be used indoors or outdoors
- · Injection-molded thermoplastic material
- Universal mounting plate; Flame-resistant and impact-resistant





Catalog Number	Description	Finish	Replaces	Coverage	Voltage	Watts	UPC
APWR2	Remote Emergency Lamps, 2 Heads	White	2-5.4W INC. Heads	17 ft.	3.6V	1W	080083608584

# **ALL-PRO** EMERGENCY LIGHTING

### **APX Series**

### **EXIT SIGNAGE**

- Economical LED exit sign for general purpose applications
- · Durable, injection-molded, thermoplastic material resists discoloration
- · Field-Selectable red or green LEDs and faces
- · Universal configurations (single and double-face); Universal mounting (ceiling, wall and end)











### MarketPro Essentials

Catalog Number	Description	Finish	Voltage	Watts	UPC
ES APX7RG	Self Powered, Unv. Red/Green	White	120/277V	1.05W at 277V	080083281107

# **APC Combo Series**

### **EMERGENCY LIGHTING**

- · Economical LED combo unit; Exit and LED emergency lighting heads
- · Durable, injection-molded, thermoplastic material resists discoloration
- · Field-Selectable red or green LEDs and faces
- Universal configurations (single and double-face); Universal mounting (ceiling, wall and end)
- · Low-voltage disconnect, Line-Latched; Brownout circuit










#### MarketPro Essentials

Catalog Number	Description	Finish	Replaces	Coverage	Voltage	Watts	UPC
ES APC7RG	2 Heads, Unv. Red/Green	White	2-5.4W Inc. Heads	17 ft.	120/277V	4.04W at 277V	080083280827

Catalog Number	Description	Finish	Replaces	Coverage	Voltage	Watts	UPC
APCH7RG	2 Heads, Unv. Red/Green, Remote Cap.	White	4-5.4W Inc. Heads	34 ft.*	120/277V	3.79W at 277V	080083280865
APC7RGSQ30	2 Sq. Heads, Unv. Red/Green	White	2 - 10W Inc. Heads	30 ft	120/277V	1.2W at 277V	080083296859
APCH7RGSQ30	2 Sq. Heads, Unv. Red/Green, Remote Cap.	White	2 - 10W Inc. Heads	47 ft*	120/277V	1.2W at 277V	080083296873

<sup>\*</sup>Egress coverage with APCH + Remote head units



# **ATLITE** EXIT SIGNAGE

# **Durable Design. Built-to-Last.**



AtLite offers durable and dependable emergency lighting and exits for commercial and industrial applications that are also approved for the New York City market.

### **RCS Combo Series**

#### **EXIT SIGNAGE**

- · New York City compliant LED combo exit sign
- · Heavy-duty, 20-gauge steel housing and face plate provides durability
- · Energy-efficient, long-life LED's; illuminated by field-replaceable LED strip
- · Single or double face with maximum of three heads for ultimate flexibility





Catalog Number	Description	Finish	Replaces	Voltage	Watts	UPC
RCS182LED	Steel Combo, 1 Face, 2 Heads	White	2 12W INC. Heads	120/277V	N/A	080083574322
RCS183LED	Steel Combo, 1 Face, 3 Heads	White	3 12W INC. Heads	120/277V	N/A	080083574308
RCS282LED	Steel Combo, Double Face, 2 Heads	White	2 12W INC. Heads	120/277V	N/A	080083574315
RCS283LED	Steel Combo, Double Face, 3 Heads	White	3 12W INC. Heads	120/277V	N/A	080083574292

### **Rival RXS Series**

#### **EXIT SIGNAGE**

- · New York City compliant steel LED exit sign
- · Heavy-duty, 20-gauge steel housing with canopy
- · Energy-efficient, long-life LED's; illuminated by field-replaceable LED strip
- Universal configurations (single- and double-face); Universal mounting (ceiling, wall and end)





Catalog Number	Description	Finish	Voltage	Watts	UPC
RXSN8RU	Steel Exit, Self Powered, Univ. Face	White	120/277V	5	080083634576

### **REL Series**

#### **EMERGENCY LIGHTING**

- · New York City compliant steel LED emergency light
- · Heavy-duty, 20-gauge steel housing and face plate for maximum durability
- · Long-lasting, high-efficiency LED heads; maintenance-free nickel cadmium battery
- · Brownout protection; low-voltage disconnect



Catalog Number	Description	Finish	Replaces	Voltage	Watts	UPC
	Steel Emergency Light, 2 Heads, 2 Remotes		2 9W INC. Heads	120/277V	5	080083574353
10REL72-LED83	Steel Emergency Light, 3 Heads, 5 Remotes	White	2 9W INC. Heads	120/277V	5	080083574339

# **ATLITE** EXIT SIGNAGE

### **ATLEMINI Series**

#### **EMERGENCY LIGHTING**

- · New York City compliant LED emergency light with 90 minutes of run time
- · Jbox and conduit knockouts for easy installation; wall or ceiling mount applications
- · Long-lasting, energy-efficient LED heads; maintenance-free nickel cadmium battery
- · Available with two or three 80 lumen rotatable heads







	COMPLIANT						
atalog Number	Description	Finish	Replaces	Coverage	Voltage	Watts	UPC
TLEMINI-2H	Steel Emergency Light, 2 Heads	White	5.4 W INC	18 ft.	120-277V	0.78 W	080083836079

# **AUX Edge-Lit Exit Series**

### **EXIT SIGNAGE**

- · Edge-Lit Exit allows seamless presence in architecturally significant surroundings
- · Labor savings self-diagnostics, New York City compliant
- · Universal mounting; Universal Lens (clear, mirror, white and single- and double-sided)
- Ordering and installation simplified as all housing and lens options are included







	COMPLIANT				
Catalog Number	Description	Finish	Voltage	Watts	UPC
AUXSSD	Unv. Self Powered, Self-Diag.	Silver	120/277V	1.1 at 277 V	080083703296
AUXSSD6	Unv. Edge Lit, Self Powered	Silver	120/277V	0.9/1.1W	080083718115
AUXSSD-SP PACK	Unv. Self Powered, Self-Diag., Single Pack	Silver	120/277V	1.1 at 277 V	080083848669

# **ACX Complete Edge Lit Exit**

#### **EXIT SIGNAGE**

- · Surface ceiling, wall, end mount, recessed ceiling and wall mount
- · Pivot housing for sloped ceiling or back wall mount
- NYC Compliant 8" letter single-sided clear and double-sided mirror lens panels included
- Battery backup models provide 90 minutes of emergency run time
- · NFPA approved field installable directional chevrons included









Catalog Number	Description	Finish	Replaces	Coverage	Voltage	Watts	UPC
ACXNOR	Self Powered, Aluminum	Satin Aluminum	N/A	N/A	120/277 V	3.14	080083277742



