

Description

The E7ICAT is a compact and efficient recessed housing optimized and listed for EISA compliant tungsten-halogen, CFL and LED lamps as well as incandescent. Housing is suitable for residential or light commercial applications. For installation in insulated ceilings* and non-insulated ceilings with airtight code compliant construction. Use with a variety of trims and finishes to create different lighting effects or to match any decor. May be retrofit with compatible HALO LED lighting systems.

| Catalog # | Туре |
|-------------|------|
| | |
| Project | |
| Comments | Date |
| | |
| Prepared by | |

Specification Features

Housing

- Single wall die-formed aluminum housing
- Housing features a precision rolled interlocking collar which maintains aperture geometry for greater assurance of installation results
- Integral Air-Tite gasket for coderequired gasket between fixture and finished ceiling - seals aperture without need for additional caulk
- May be removed from the plaster frame to provide access to junction box

Socket Plate

- Rigid socket plate adjusts and locks without tools for various lamp sizes.
- Socket plate and bracket may be removed when using socket supporting trims

Plaster Frame

- Galvanized steel frame. Housing adjusts in plaster frame to accommodate up to 3/8" - 1" ceiling thickness
- (2) Regressed locking screws for securing hanger bars
- Integral Air-Tite gasket seals housing and meets code-required gasket between fixture and finished ceiling

Includes:

Bar Hangers All Nail!™

- Integral precisely positioned nail for engineered and natural framing
- Mini-foot leveling flange
- Integral T-Grid Clip, no accessory clips required

q-Channel bars with Pass-N-Thru $^{\mbox{\tiny TM}}$

- Unique inverted "q" interlocking channel for rigidity and stability
- Pass-N-Thru[™] feature allows bars to cross-over for tool-less shortening in tight spaces

Hinged junction box w/ Slide-N-Side™

- (3) Slide-N-Side™ Non-Metallic (NM) wire traps, allow wiring outside the hox
- For 14-2, 14-3, 12-2, 12-3 U.S. and 14-2, 14-3, 12-2 Canadian
- (4) 1/2" conduit pry-outs
- · Hinged door for easy access
- Box is repositionable 90° on frame to avoid obstructions

Quick Connect™

- (3) Push wire nuts included, for speed & reliability
- Clear caps for wire connection visibility

cULus Listed

- Compact 16 in³ volume
- Listed for max. (10) No. 12 AWG or (14) No. 14 AWG 90° C splice conductors in box

Air-Tite™ code compliant

- Certified under ASTM E283
- Exclusive gasket seals aperture, frame & ceiling
- · No additional caulk required

Socket

- Porcelain socket with nickel plated brass screw shell
- Snap-in springs secure socket to socket plate, and may be detached when using socket supporting trims

Thermal Protector

 Self resetting thermal protector deactivates fixture if overheating occurs due to improper lamping

Trims

 Halo Fit-All concept offers multiple trim options in a variety of design styles, and functional beam distributions to control beam angle and lumen delivery in accommodating various lamp types including Halogen, CFL and LED

Compliance

- cULus Listed 1598 Luminaire
- · cULus Listed Damp Location
- cULus Listed for Wet Location, covered ceiling, with select trims
- cULus Listed for direct contact with insulation and combustible material*
- Air-Tite code compliant. Certified under ASTM E283; not exceeding 2.0 cfm (0.944 L/s) air leakage rate tested at a 1.57 psf (75 Pa) pressure differential
- · RoHS compliant
- *Not to be used in direct contact with spray foam insulation (Consult NEMA LSD57-2013)









E7ICAT


6" IC, Air-Tite, New Construction Housing


E26 Screw base housing

FOR USE IN INSULATED CEILINGS

FOR DIRECT CONTACT WITH INSULATION*

Dimensions





Special Features

All-Nail!™ bar hangers q-Channel bars with Pass-N-Thru™ Hinged J-Box with Slide-N-Side™ Quick Connect™ push wire nuts Air-Tite™ code compliant



Ordering Information

Sample Number: E7ICAT 6110WB

Order housing, trim and lamp (by others) separately for a complete luminaire.

E7ICAT = 6" insulated ceiling, airtight recessed housing, new construction, 120V

Trims

Reflectors



30 Reflector, Self-flange

OD: 7-1/4" [184mm]
30HAT=Haze Reflector, White Trim 30RGAT=Residential Gold Reflector, White Trim 30CAT=Clear Specular Reflector, White Trim



30SBAT Reflector, Self-flange

OD: 7-1/4" [184mm] 30SBAT=Black Specular Reflector, Self-flange



404 Specular Reflector

OD: 7-1/4" [184mm]

404C=Clear Specular Reflector, White Trim 404H=Haze Reflector, White Trim 404SN=Satin Nickel Reflector and Trim 404TBZ=Tuscan Bronze Reflector and Trim



426 Reflector Cone OD: 7-1/4" [184mm]

426=Clear Specular Reflector Cone, White Trim 426MB=Black Specular Reflector Cone, White Trim

426H=Haze Reflector Cone, White Trim 426SN=Satin Nickel Reflector Cone and Trim 426TBZ=Tuscan Bronze Reflector Cone and Trim



429 Dayform White Cone OD: 7-1/4" [184mm]

429P=White Reflector and Trim



4041 White Reflector, Self-flange

OD: 7-1/4" [184mm] 4041P=White Reflector and Trim



4261 White Reflector Cone, Self-flange OD: 7-1/4" [184mm]

4261P=White Reflector and Trim



6106 Straight Reflector Cone, Self-flange

OD: 7-3/4" [197mm] 6106SC=Specular Reflector, White Trim



6107 Tapered Reflector, Self-flange

OD: 7-3/4" [197mm] 6107SC=Specular Reflector, White Trim





6120 Full Cone Reflector, Self-flange OD: 7-3/4" [197mm]

6120WH=White Reflector and Trim 6120SN=Satin Nickel Reflector and Trim

6120TBZ=Tuscan Bronze Reflector and Trim



6121 Shallow Full Cone Reflector, Self-flange

OD: 7-3/4" [197mm]

6121WH=White Reflector and Trim



30 Baffle, Self-flange

OD: 7-1/4" [184mm]
30WAT=White Baffle, Reflector and Trim 30WATH=White Baffle, Clear Reflector and White Trim

30PAT=Black Baffle, Clear Reflector and White Trim

30SNAT=Satin Nickel Baffle, Reflector and Trim 30TBZAT=Tuscan Bronze Baffle, Reflector and



310 Coilex® Baffle OD: 7-1/4" [184mm]

310W=White Coilex Baffle and Trim 310P=Black Coilex Baffle, White Trim

310SN=Black Coilex Baffle, Satin Nickel Trim 310TBZ=Black Coilex Baffle, Tuscan Bronze Trim



312 Coilex® Baffle OD: 7-1/4" [184mm]

312W=White Coilex Baffle and Trim 312P=Black Coilex Baffle, White Trim



353 Metal Baffle

OD: 7-1/4" [184mm]

353SN=Satin Nickel Baffle and Trim 353TBZ=Tuscan Bronze Baffle and Trim



6100 Tapered Metal Baffle with (2) Trim Rings OD: 7-1/8" [181mm]

6100WB=White Baffle, Narrow and Wide White

Trims (included) 6100BB=Black Baffle, Narrow and Wide White Trims (included)



6101 Straight Metal Baffle with (2) Trim Rings OD: 7-1/8" [181mm]

6101WB=White Baffle, Narrow and Wide White Trims (included)

6101BB=Black Baffle, Narrow and Wide White Trims (included)



6102 Tapered Metal Baffle, Self-flange

OD: 7-3/4" [197mm]

6102WB=White Baffle and Trim 6102BB=Black Baffle, White Trim



6103 Straight Metal Baffle, Self-flange

OD: 7-3/4" [197mm] 6103WB=White Baffle and Trim

6103BB=Black Baffle, White Trim



6108 Coilex[®] Straight Plastic Baffle, Self-flange OD: 7-3/4" [197mm] 6108WB=White Plastic Straight Coilex Baffle,

White Trim

6108BB=Black Plastic Straight Coilex Baffle, White Trim

6108BKBB=Black Plastic Straight Coilex Baffle, Black Trim



6109 Coilex® Tapered Baffle, Self-flange OD: 7-3/4" [197mm]

6109WB=White Tapered Coilex Baffle,

White Trim 6109BB=Black Tapered Coilex Baffle,

White Trim

6109BKBB=Black Tapered Coilex Baffle, Black Trim



6110 Perftex Baffle, Self-flange OD: 7-3/4" [197mm] 6110WB=White Perftex Baffle and Trim

6110BB=Black Perftex Baffle, White Trim 6110BKBB=Black Perftex Baffle and Trim



<u>6125 Full Cone Baffle, Self-flange</u>

OD: 7-3/4" [197mm] 6125WB=White Baffle and Trim 6125BB=Black Baffle, White Trim 6125BKBB=Black Baffle and Trim



6126 Shallow Full Cone Baffle, Self-flange

OD: 7-3/4" [197mm] 6126WB=White Baffle and Trim

6126BB=Black Baffle, White Trim





74 PAR30 Eyeball 30° Tilt, Self-flange OD: 8" [203mm] 74P=White Eyeball and Trim



76 PAR38 Gimbal 30° Tilt, Self-flange

OD: 8" [203mm] 76P=White Gimbal and Trim



78 BR/PAR30 Eyeball 30° Tilt, Self-flange

OD: 8" [203mm]

78P=White Eyeball and Trim 78PAT=White Eyeball and Trim, Air-Tite 78SN=Satin Nickel Eyeball and Trim 78TBZ=Tuscan Bronze Eyeball and Trim



376 PAR30 Regressed Gimbal 30° Tilt,

Self-flange OD: 7-1/4" [184mm] 376W=White Baffle and Trim 376P=Black Baffle and White Trim



378 PAR30 Regressed Gimbal with Splay 25° Tilt,

Self-flange OD: 7-1/4" [184mm]

378P=White Splay and Trim 378=Clear Specular Splay and White Trim



420 BR/PAR30 Regressed Eyeball 30° Tilt,

Self-flange
OD: 7-1/4" [184mm]
420W=White Eyeball, Baffle and Trim 420P=White Eyeball, Black Baffle, White Trim



478 PAR38 Adjustable Regressed Gimbal with

Splay 25° Tilt, Self-flange OD: 7-1/4" [184mm]

478P=White Splay and Trim



6130 BR/PAR30 Eyeball 35° Tilt, Self-flange OD: 7-3/4" [197mm]

6130WH=White Eyeball and Trim

6170 PAR38 Gimbal 25° Tilt, Self-flange

OD: 7-3/4" [197mm] 6170WH=White Gimbal and Trim 6170BK=Black Gimbal and Trim

6170SN=Satin Nickel Gimbal and Trim 6170TBZ=Tuscan Bronze Gimbal and Trim



6215 PAR30 Double Gimbal 35°-50° Tilt, Self-flange OD: 7-3/4" [197mm]

6215WH=White Gimbal and Trim

6215BK=Black Gimbal and Trim 6215SN=Satin Nickel Gimbal and Trim 6215TBZ=Tuscan Bronze Gimbal and Trim



6222 Regressed PAR30 Adjustable 45° Tilt,

Self-flange OD: 7-3/4" [197mm]

6222WB=White Baffle and Trim

6222BB=Black Baffle and Trim 6222SC=Specular Clear Reflector, White Trim 6222H=Haze Reflector, White Trim

Lenses & Wet Location Showerlights

170 Albalite Lens with Reflector

OD: 8" [203mm] 170P=Frosted Albalite Glass Lens, White Trim 170PS=Frosted Albalite Glass Lens, White Plastic Trim, Showerlight, Air-Tite



171P=Drop Opal Glass Lens, White Trim 171PS=Drop Opal Glass Lens, White Plastic Trim, Showerlight, Air-Tite




OD: 7-3/4" [197mm]

172PS=Frosted Glass Dome, White Plastic Trim 172SNS=Frosted Glass Dome, Satin Nickel Plastic Trim

172TBZS=Frosted Glass Dome, Tuscan Bronze Plastic Trim

continued





Ordering Information

Sample Number: E7ICAT 6110WB

Order housing, trim and lamp (by others) separately for a complete luminaire.

E7ICAT = 6" insulated ceiling, airtight recessed housing, new construction, 120V

Trims

Lenses & Wet Location Showerlights



173 Fresnel Lens with Reflector

OD: 8" [203mm]

173P=Fresnel Glass Lens, White Trim 173PS=Fresnel Glass Lens, White Plastic Trim, Showerlight, Air-Tite

6145 Open Wet Location, Shallow Reflector, Self-flange - Showerlight* OD: 7-3/4" [197mm]

6145WH=White Reflector and Trim 6145SN=Satin Nickel Reflector and Trim 6145TBZ=Tuscan Bronze Reflector and Trim



6146WH=White Reflector and Trim 6146SN=Satin Nickel Reflector and Trim 6146TBZ=Tuscan Bronze Reflector and Trim

6150 Frost Dome Glass Lens, Self-flange

OD: 7-3/4" [197mm]

6150WH=Frost Dome Glass Lens with Reflector, White Plastic Trim

6150SN=Frost Dome Glass Lens with Reflector, Satin Nickel Plastic Trim

6150TBZ=Frost Dome Glass Lens with Reflector, Tuscan Bronze Plastic Trim

6162 Drop Opal Plastic Lens, Self-flange -

Showerlight OD: 7-3/4" [197mm]

6162WH=Drop Opal Plastic Lens with Reflector, White Plastic Trim

6230 Squircle Frost Glass Lens,

Metal Trim - Showerlight
OD: 7-1/4" [183mm]
6230AH=Frost Glass Lens, Aluminum Haze Squircle Trim

6230PN=Frost Glass Lens, Polished Nickel

Squircle Trim

6230SN=Frost Glass Lens, Satin Nickel

Squircle Trim 6230TBZ=Frost Glass Lens, Tuscan Bronze Squircle Trim



6255 Soft Square, Frost Curve Glass Lens,

Self-flange - Showerlight
OD: 7-1/4" [183mm]
6255WH=Frost Curve Glass Lens with Reflector, White Plastic Trim

6255SN=Frost Curve Glass Lens with Reflector,

Satin Nickel Plastic Trim

6255TBZ=Frost Curve Glass Lens with Reflector, Tuscan Bronze Plastic Trim

Open, Splay & Wall Wash

300 Open Trim with Fixed Socket Bracket,

Self-flange OD: 7-1/4" [183mm]

300P=Self-flange with White Open Trim 300SN=Self-flange with Satin Nickel Open Trim 300TBZ=Self-flange with Tuscan Bronze Open Trim

327 White Splay Trim with Fixed Socket

Bracket, Self-flange OD: 7-3/4" [197mm]

327P=White Splay Trim with Socket Bracket



328 White Splay Trim OD: 7-3/4" [197mm]

328P=White Splay Trim



430 Wall Wash with Baffle & Full Reflector

OD: 7-1/4" [183mm] 430W=White Baffle, with Upper Reflector, White Trim

430P=Black Baffle, with Upper Reflector, White Trim

*Outdoor rated lamp only (purchase separately)

