

Project		Catalog #		Type	
Prepared by		Notes		Date	



# Metalux

## OHB LED High Efficacy

### LED High Bay Efficiency Luminaire

#### Typical Applications

Industrial • Commercial • Manufacturing • Food Processing • Sports / Multi-Purpose

#### Interactive Menu

- Order Information [page 2](#)
- Photometric Data [page 3](#)
- Connected Systems [page 5](#)
- Product Warranty

#### Product Certification



#### Product Features




#### Top Product Features


- Precision designed optical performance
- Offered in both standard and high efficacy versions
- High performance efficacy up to 210 lm/W
- Efficient 1-for-1 replacement of linear fluorescent & HID fixtures
- Lumen packages – 12K, 15K, 18K, 24K, 30K, 36K, 48K, 60K
- Narrow, medium, and wide distribution

#### Dimensional and Mounting Details


OHB-12HE, 15HE, 18HE




OHB-24HE, 30HE



OHB-48HE, 60HE



OHB-36HE



[additional product diagrams](#)

## Order Information

SAMPLE ORDER NUMBER: **OHB-24HE-MFL-UNV-L840-CD-U** Includes V Hangers for rapid installation

Series	Revision	Lumen Packages/ High Efficacy	Distribution/Shielding	Voltage	CCT/CRI
Series <sup>(1), (2)</sup>	Revision	Lumen Packages / High Efficacy	Distribution/Shielding	Voltage <sup>(5), (6), (7)</sup>	CCT/CRI
<b>OHB</b> =Optimized High Bay	<b>[Blank]</b>	<b>12HE</b> =12,000 Lumens <b>15HE</b> =15,000 Lumens <b>18HE</b> =18,000 Lumens <b>24HE</b> =24,000 Lumens <b>30HE</b> =30,000 Lumens <b>36HE</b> =36,000 Lumens <b>48HE</b> =48,000 Lumens <b>60HE</b> =60,000 Lumens <sup>(3)</sup>	<b>N</b> =Narrow <b>MFL</b> =Medium Frosted <b>MCL</b> =Medium Clear <b>W</b> =Wide <b>NL</b> =No Lens <sup>(4)</sup>	<b>120V</b> =120 Volt <b>277V</b> =277 Volt <b>347V</b> =347 Volt <b>480V</b> =480 Volt <b>UNV</b> =Universal Voltage 120-277 <b>UNC</b> =Universal Voltage 347/480	<b>L730</b> =70CRI / 3000K <b>L735</b> =70CRI / 3500K <b>L740</b> =70CRI / 4000K <b>L750</b> =70CRI / 5000K <b>L830</b> =80CRI / 3000K <b>L835</b> =80CRI / 3500K <b>L840</b> =80CRI / 4000K <b>L850</b> =80CRI / 5000K <b>L930</b> =90CRI / 3000K <b>L935</b> =90CRI / 3500K <b>L940</b> =90CRI / 4000K <b>L950</b> =90CRI / 5000K
<b>Notes</b> (1) To order product that is compliant with the Buy American Act of 1933 (BAA) or Trade Agreements Act (TAA), use the online specification configurator to specify BAA or TAA. Please refer to <a href="#">DOMESTIC PREFERENCES LINK</a> for more information. (2) DesignLights Consortium® Qualified and classified for both DLC Standard and DLC Premium, refer to <a href="#">www.designlights.org</a> for details.		<b>Notes</b> (3) 60HE configuration not available with the combination of Sensors or EBP plus 347V, 480V, or UNC.	<b>Notes</b> (4) NL (Non Lensed) versions not available with 36HE, 48HE, and 60HE lumen packages.	<b>Notes</b> (5) Voltage must be specified when ordered with plugs or emergency drivers. (6) When ordering sensors option, specify as UNV (for 120V or 277V), 347V or 480V. (7) Ambient temperatures limited to 40C when using emergency, sensors, or 5LTD in conjunction with 347V or 480V.	

Options	Driver Type	Wiring	Options	Packaging
Options	Driver Type	Wiring	Options	Packaging
<b>EBP/TD</b> <b>EL20W</b> =20-watt 120V-277V emergency battery pack installed <sup>(8), (9), (12)</sup> <b>EL20-W-REM</b> =20-watt 120V-277V emergency battery pack remote mounted <sup>(8), (9), (11)</sup> <b>GTR2</b> =Bodine Generator Transfer Device <sup>(11)</sup> <b>ETRD</b> =Iota Emergency Transfer Relay with dimming control <sup>(10)</sup>	<b>CD</b> =0-10V Dimming Driver <b>5LTD</b> =Fifth Light DALI <sup>(13), (14)</sup>	<b>C3 (1)</b> =1 Circuit, 3' Cord with no Plug <b>C3 (2)</b> =2 Circuits, 3' Cord with no Plug <b>C6 (1)</b> =1 Circuit, 6' Cord with no Plug <b>C6 (2)</b> =2 Circuits, 6' Cord with no Plug <b>PC3/120</b> =(NEMA L5-15P) 3' Cord with NEMA Plug <b>PC3/277</b> =(NEMA L7-15P) 3' Cord with NEMA Plug <b>PC3/347</b> =(NEMA L24-20P) 3' Cord with NEMA Plug <b>PC3/480</b> =(NEMA L8-20P) 3' Cord with NEMA Plug <b>PC6/120</b> =(NEMA L5-15P) 6' Cord with NEMA Plug <b>PC6/277</b> =(NEMA L7-15P) 6' Cord with NEMA Plug <b>PC6/347</b> =(NEMA L24-20P) 6' Cord with NEMA Plug <b>PC6/480</b> =(NEMA L8-20P) 6' Cord with NEMA Plug	<b>MP</b> =Modular Plug <sup>(16)</sup> <b>PAF</b> =Painted After Fabrication <b>HA</b> =High Ambient <sup>(17), (18)</sup> <b>Motion Sensors</b> <b>MS</b> =360° or 180° Motion Sensor Installed, (specify voltage) <sup>(15)</sup> <b>SVPD3</b> =Integrated Occupancy and Daylight Dimming Sensor, 1200 sq. ft. coverage <sup>(15)</sup> <b>OEFP010VMV</b> =Occupancy Sensor with Integrated Photocell <sup>(15)</sup> <b>FSP-211/L7-U</b> =PIR Occupancy Sensor with Integral 0-10V Dimming <sup>(15)</sup> <b>LWR</b> =Enlighted Wireless Sensor system <sup>(15)</sup> <b>ZW-SWPD3</b> =Integrated Wavelinx Wireless Sensor, 1200 sq ft. coverage <sup>(15)</sup> <b>ZW</b> =WaveLinX Wireless Ready (does not include sensor) <sup>(15)</sup>	<b>U</b> =Unit Pack <b>PALC</b> =Job Pack, in carton
<b>Notes</b> (8) With integral test switch/indicator/laser test. For approximate delivered lumens multiply the lumens per watt of the desired fixture by the wattage of the emergency battery pack. (9) EM options available in 0°C - 45°C ambient. (10) Used to transfer fixture to secondary power during outage. Must be used in conjunction with UL 1008 device (provided by others). These options require 2 relays on fixtures with dimming drivers. ETRD option only requires one relay when used on a dimming fixture. A maximum of two devices can be used on one product. (11) GTR2 option is only available with 4ft fixtures (36K, 48K, and 60K lumens). (12) High Ambient not available with integrated emergency.	<b>Notes</b> (13) Sensor or UNC not available in conjunction with 5LTD driver. (14) Ambient temperatures limited to 40C when using emergency, sensors, or 5LTD in conjunction with 347V or 480V.		<b>Notes</b> (15) When ordering sensor or EBP/TD option, specify as UNV (for 120V or 277V), 347V or 480V. (16) Requires use of MC or MPC cord accessories, specify voltage for plugs (MP). (17) High Ambient not available with integrated emergency. (18) Refer to Ambient Chart for temperature ratings.	

## Accessories

Accessories (order separately)
<b>OHB-WG162</b> =Wire guard for 12HE, 15HE, and 18HE <b>OHB-WG222</b> =Wire guard for 24HE and 30HE <b>OHB-WG164</b> =Wire guard for 36HE <b>OHB-WG224</b> =Wire guard for 48HE and 60HE <b>Y-TOGGLE</b> =Y Mounting Toggle, #2 Cable (Specify 10' or 30', requires 2 per fixture) <b>FH-1</b> =Fixture Hook <sup>(20)</sup> <b>FL-1</b> =Fixture Loop <sup>(20)</sup> <b>OHB-SPM</b> =Single Point Mounting Hub <sup>(19)</sup> <b>MPC3</b> =3' Modular Power Cord & Plug (Specify Voltage) <b>MPC6</b> =6' Modular Power Cord & Plug (Specify Voltage) <b>MC3</b> =3' Modular Power Cord <b>MC6</b> =6' Modular Power Cord <b>SWPD3</b> =WaveLinX Wireless Sensor (to be installed with "ZW" sensor ready fixtures only)
<b>Notes</b> (19) OHB-SPM mounting not available with EL20W or ETRD options. (20) Must be used in conjunction with OHB-SPM accessory for proper installation.

## Product Specifications

### Construction

- Rugged and durable scalable design with rigid, steel center channel
- Mechanically attached end caps provide strength and durability
- Suspension mounting with optional wire hook and chain set or cable; Single monopoint mounting with SPM tong hanger

### Electrical

- Long-Life LED system coupled with electrical driver for optimal performance
- LED's available in 3000K, 3500K, 4000K and 5000K with 70 CRI, 80 CRI and 90 CRI options
- Electronic drivers are available for 120-277V, 347V and 480V applications
- 0-10V dimming control (standard)
- Operating temperature of -40°C to 55°C (refer to chart)

### Emergency Battery Pack Option

- 20-watt, 120-277V integral emergency battery pack available to meet critical life-safety lighting requirements
- 90-minute batteries provide constant power to the LED system, ensuring code-compliance
- Emergency/generator transfer options available (see ordering information for details)

### Optics

- Precision designed optics deliver even illumination
- Offered in Narrow, medium and wide distributions

### Shielding

- Standard lensing provides additional LED protection and optical control
- Optional wire guards available for more complex environments

### Controls

- Integral occupancy sensor (SVPD3) option provides 600 sq. ft. to up to 1250 sq. ft. of coverage for occupancy sensing and daylight harvesting
- Integral 360° or 180° motion sensor
- Integrated Wavelinx Wireless Sensor option provides 1200 sq. ft. coverage
- Wavelinx wireless enabled (does not include sensor)

### Finish

- White enamel finish preceded by a multistage cleaning cycle
- Iron phosphate coating with rust inhibitor protects against contaminants and oxidation


### Compliance

- cULus listed for damp locations
- LED modules comply with IESNA LM-79 and LM-80 standards
- DesignLights Consortium® Qualified and classified for both DLC Standard and DLC Premium (refer to [www.designlights.org](http://www.designlights.org) for details)

### Warranty


- Five year warranty standard.

## Photometric Data

[View IES files](#)



### OHB-24HE-MCL-UNV-L850-CD-U

Electronic Driver  
 Linear LED 5000K  
 Spacing criterion: (||) 1.3 x mounting height,  
 (⊥) 1.27 x mounting height  
 Lumens: 24645  
 Input Watts: 132W  
 Efficacy: 186.7 LPW  
 Test Report: OHB-24HE-MCL-UNV-L850-CD-U.IES




### OHB-24HE-MFL-UNV-L850-CD-U

Electronic Driver  
 Linear LED 5000K  
 Spacing criterion: (||) 1.2 x mounting height,  
 (⊥) 1.28 x mounting height  
 Lumens: 23894  
 Input Watts: 132W  
 Efficacy: 181 LPW  
 Test Report: OHB-24HE-MFL-UNV-L850-CD-U.IES



### OHB-24HE-N-UNV-L850-CD-U

Electronic Driver  
 Linear LED 5000K  
 Spacing criterion: (||) 1.51 x mounting height,  
 (⊥) 0.53 x mounting height  
 Lumens: 24029  
 Input Watts: 132W  
 Efficacy: 182 LPW  
 Test Report: OHB-24HE-N-UNV-L850-CD-U.IES



### OHB-24HE-W-UNV-L850-CD-U

Electronic Driver  
 Linear LED 5000K  
 Spacing criterion: (||) 1.16 x mounting height,  
 (⊥) 2.19 x mounting height  
 Lumens: 24377  
 Input Watts: 132W  
 Efficacy: 184.7 LPW  
 Test Report: OHB-24HE-W-UNV-L850-CD-U.IES

## Energy and Performance Data

OHB - High Efficacy 5000K 70CRI											
Catalog Number	Lumen Output					Watts	Efficacy (LPW)				
	N	MFL	MCL	W	NL	277V	N	MFL	MCL	W	NL
OHB-12HE	13045	12971	13379	13234	13907	68	193	192	198	196	206
OHB-15HE	16113	16022	16526	16346	17178	83	193	192	198	196	206
OHB-18HE	19594	19484	20097	19879	20890	102	192	191	197	195	204
OHB-24HE	25526	25383	26181	25896	27214	132	194	193	199	197	207
OHB-30HE	32410	32228	33241	32880	34552	172	189	188	194	191	201
OHB-36HE	38345	38129	39328	38901	–	201	190	189	195	193	–
OHB-48HE	51874	51583	53205	52626	–	261	199	197	204	201	–
OHB-60HE	62913	62560	64527	63825	–	333	189	188	194	192	–

OHB - High Efficacy 5000K 80CRI											
Catalog Number	Lumen Output					Watts	Efficacy (LPW)				
	N	MFL	MCL	W	NL	277V	N	MFL	MCL	W	NL
OHB-12HE	12279	12210	12594	12457	13091	68	182	181	187	185	194
OHB-15HE	15167	15082	15557	15387	16170	83	182	181	187	185	194
OHB-18HE	18445	18341	18918	18712	19664	102	180	179	185	183	192
OHB-24HE	24029	23894	24645	24377	25617	132	183	182	187	185	195
OHB-30HE	30509	30337	31291	30951	32525	172	178	177	182	180	189
OHB-36HE	36095	35893	37021	36619	–	201	179	178	184	182	–
OHB-48HE	48831	48557	50084	49539	–	261	187	186	192	190	–
OHB-60HE	59222	58890	60742	60081	–	333	178	177	182	180	–

## Ambient Ratings

Lumen Package	Ambient Rated	(HA) High Ambient	EM
OHB-12HE	55°C	–	45°C
OHB-15HE	55°C	–	45°C
OHB-18HE	45°C	55°C	45°C
OHB-24HE	55°C	–	45°C
OHB-30HE	55°C	–	45°C
OHB-36HE	45°C	55°C	45°C
OHB-48HE	55°C	–	45°C
OHB-60HE	55°C	–	45°C

## Energy Data

Input Watts:
12HE (12,000 lumens)=68W
15HE (15,000 lumens)=83W
18HE (18,000 lumens)=120W
24HE (24,000 lumens)=132W
30HE (30,000 lumens)=172W
36HE (36,000 lumens)=2101W
48HE (48,000 lumens)=263W
60HE (60,000 lumens)=334W

## Shipping Data

Catalog No.	Wt.
OHB-12HE	10 lbs.
OHB-15HE	13 lbs.
OHB-18HE	13 lbs.
OHB-24HE	13 lbs.
OHB-30HE	16 lbs.
OHB-36HE	20 lbs.
OHB-48HE	20 lbs.
OHB-60HE	20 lbs.

## Modular Power Supply Option

Modular Power Supply option is available for use with all F-Bay products. The modular power supply allows external fixture access for safe and easy servicing. There is no need to remove lamps or reflectors to disconnect fixture power with Modular Power Supply. Access to the individual fixture's power supply allows servicing without turning off all the fixtures, disrupting occupants. F-Bay Modular Power Supply is a time saver in installation – **simply plug & power.**



1. Modular Power Supply Receptacle supplied mounted into fixture Access Plate.
2. Modular Power Cord & Plugs in 120, 277, 347, & 480V configurations for easy plug & power into existing supply.

No internal fixture access required for installation or disconnecting power.

## Code Compliance

- UL/cUL Certified for Make/Break under load (UL2549)
- Meets NEC requirements for ballast disconnect (NEC 410.73G)
- Receptacle complete with insulating/dust cap

## Lumen Maintenance

Ambient Temperature	TM-21 Lumen Maintenance (60,000 hours)	Theoretical L70 (Hours)
25°C	> 96%	> 240,000

### Control Systems

- WaveLinx Wireless
- WaveLinx Wired
- WaveLinx Lite



Connected Systems  
[CLICK HERE](#)

## Systems comparison chart

Cooper Lighting Solutions provides many lighting system solutions designed to satisfy code requirements and meet the unique needs of any project.



**Standalone**



**Controlled**  
WaveLinx Lite



**Connected**  
WaveLinx Wireless



**Enterprise**  
Trellix

	Standalone	Controlled WaveLinx Lite	Connected WaveLinx Wireless	Enterprise Trellix
<b>Occupancy</b>	Yes	Yes	Yes	Yes
<b>Daylighting</b>	Yes	Yes	Yes	Yes
<b>Gateways</b>	–	–	1 WAC	300 WACs
<b>Devices</b>	–	50 per Area (1400 per site)	150 per WAC	45,000 per Core Enterprise
<b>Software</b>	–	WaveLinx Lite Mobile App	WaveLinx Mobile App	Trellix Core
<b>Areas</b>	–	28 per Site	16 per WAC	up to 4,800
<b>Zones</b>	–	16 per Area	16 per Area	up to 76,800
<b>Scheduling</b>	–	–	Local	Global
<b>VividTune™</b>	–	–	Yes	Yes
<b>Plug-Load Control</b>	–	–	Yes	Yes
<b>Low-Voltage Power</b>	–	–	Yes	Yes
<b>Integration</b>	–	–	–	BACnet, API
<b>Dashboards</b>	–	–	–	Energy, Occupancy
<b>Configuration</b>	–	Installer	Technician	Technician / IT

## SCALABILITY

devices






areas

floors






buildings

## Dimensional and Mounting Details





### OHB-12HE, 15HE, 18HE



### OHB-36HE



### OHB-24HE, 30HE



### OHB-48HE, 60HE

