DESCRIPTION

**HALO®** 

Low voltage Perforated Shade lampholders for use with 12V MR16 lamps. L2702 has integral 12V Electronic transformer, L2701 must be used with L2001 electronic transformer (order separately). For use with Halo Power-Trac systems except Four-Circuit track.

Catalog #	Туре
Project	
Comments	
Comments	
Prepared by	Date

# SPECIFICATION FEATURES

# A...Electrical Quick Lock Adapter/Transformer

Polycarbonate casing.
Attaches electrically and mechanically anywhere along Power-Trac. L2702 includes integral 12V Electronic transformer. Visual polarity line assures proper grounding. Two position conductor allows

L2701

use in single circuit and either circuit of two circuit track.

# **B**···Body

Die cast metal lampholder body with perforated shade. Shade includes tempered glass safety shield.

# C... Stem

Stem allows lampholder to rotate 338° and adjust vertically from 0° to 90°.

# Listings

UL listed and CSA certified for use with Halo and Lazer-by-Halo track and track systems.



L2701




L2702

# LOW VOLTAGE PERFORATED SHADE LAMPHOLDERS

Power-Trac®

# A C W W



# ORDERING INFORMATION SAMPLE NUMBER: L2701P

Lampholders Finishes

L2701 P=White
L2702 MB=Matte Black



# L2701

For use with: Up to 50W 12V MR16

L =3" [76mm] W=3 1/4" [83mm] E =6 1/8" [137mm]

# Accessories

L2001 12V Transformer (Required for operation) NOTE: NOTFORUSE WITH FOURCIBCUIT TRACK



# 1 2702

For use with: Up to 75W 12V MR16 L =3" [76mm] W=3 1/4" [83mm]

W=3 1/4" [83mm] E =7 1/4" [184mm] T =5 1/4"

NOTE: NOT FOR USE WITH FOUR CIRCUIT TRACK

# ENERGY DATA L2701 WITH L2001

Transformer Type: Electronic Line Amps: 0.45A Total input Watts: 52W Power Factor: >0.95 THD: <20%

# L2702

Transformer Type: Electronic Line Amps: 0.61A Total input Watts: 72W Power Factor: >0.95 THD: <25%

ADV990336

# L20001 Solid State Adapter

Notes: For use with 120V Trac and L2760 Lampholders. Other lampholders will not function if they are inserted into L2001. Not for use with Four Circuit Power-Trac. 50W max.

Color Code: P, MB

